

## 9A4/9A8/992 to 985/973 CAN Interface Wiring

985/973	4-way Connector Superseal/Sureseal	Description	9A4/9A8/992
16	Pin 1	IGN 12v	N/A
4	Pin 2	Power Ground	N/A
14	Pin 3	CAN Low	Pin 8
6	Pin 4	CAN High	Pin 9

### 9A4/9A8/992 Engine Harness Half

Uses Tyco Electronic/AMP Superseal connector. Available from RS Components. You require 4-way tab housing, part no. 314-1277 (packs of 5). You will also require receptacles (female) 0.35 - 0.50 wire is 314-1334 (packs of 100).

### 985/973 Adaptor Half

Uses Tyco Electronic/AMP Superseal connector. Available from RS Components. You require the 4-way receptacle housing part no. 314-1211 (packs of 5). You will also require tab (male), 0.35 - 0.50 wire part no. 314-1312 (packs of 100).

Note: Seals to make these connectors maintain IP67 sealing, you require wire seals part no. 314-1176.



SBD Motorsport Ltd  
Unit 15, Red Lion Business Park, Red Lion Road, Surbiton,  
Surrey. KT6 7QD  
Tel:0208 391 0121  
Website: [www.sbdmotorsport.co.uk](http://www.sbdmotorsport.co.uk)

 SBDMotorsport

 sbdevelopments