

## **TIGHTENING METHOD**

### **BLT-STUD-DUR-2.0L**

#### **Head stud kit.**

ISSUE DATE: July 2008

**NOTE -USE A STANDARD HEAD GASKET WITH THIS KIT**

---

## **METHOD**

**ARP lubricant must be used on all threads and underneath face of nut and washer.**

### **BEFORE CYLINDER HEAD IS INSTALLED: -**

- 1. Ensure threads in block & on stud are completely clean**
- 2. Apply lubricant to stud threads & screw stud into block finger tight only.**

**Once cylinder head is installed, fit nut & washer then: -**

**STAGE 1---25 LB/FT**

**STAGE 2---Back off ½ turn**

**STAGE 3---25 LB/FT**

**STAGE 4---60 LB/FT**

**STAGE 5---Back off ¼ turn**

**STAGE 6---60 LB/FT**

# DURATEC HEAD STUD TIGHTENING SEQUENCE

<b>8</b>	<b>4</b>	<b>1</b>	<b>5</b>	<b>9</b>
<b>7</b>	<b>3</b>	<b>2</b>	<b>6</b>	<b>10</b>

# DURATEC HEAD STUD REMOVAL SEQUENCE

<b>3</b>	<b>7</b>	<b>10</b>	<b>6</b>	<b>2</b>
<b>4</b>	<b>8</b>	<b>9</b>	<b>5</b>	<b>1</b>

*Please be aware that Technical Support involving our Technicians is chargeable*



SBD Motorsport Ltd  
Unit 15, Red Lion Business Park, Red Lion Road, Surbiton, Surrey.  
KT6 7QD  
Tel: 0208 391 0121  
Website: [www.sbdmotorsport.co.uk](http://www.sbdmotorsport.co.uk)

 SBDMotorsport  
 sbdevelopments