

## VLSK-VX2-01K (VLC-VX04 & VLS-2.0-XE-DB01 & VLP-9K)

| Valve Lift (mm) | Installed Height (mm) | Lb          | Notes               |
|-----------------|-----------------------|-------------|---------------------|
| -2.0            | 31.0                  | 55.6        |                     |
| -1.5            | 31.5                  | 60.0        |                     |
| -1.0            | 32.0                  | 64.8        |                     |
| -0.5            | 32.5                  | 69.6        |                     |
| 0.0             | 33.0                  | 74.4        | Base Line           |
| 0.5             | 32.5                  | 79.0        |                     |
| 1.0             | 32.0                  | 84.0        |                     |
| 1.5             | 31.5                  | 88.6        |                     |
| 2.0             | 31.0                  | 93.6        |                     |
| 2.5             | 30.5                  | 98.2        |                     |
| 3.0             | 30.0                  | 103.0       |                     |
| 3.5             | 29.5                  | 108.2       |                     |
| 4.0             | 29.0                  | 112.8       |                     |
| 4.5             | 28.5                  | 117.6       |                     |
| 5.0             | 28.0                  | 122.8       |                     |
| 5.5             | 27.5                  | 127.8       |                     |
| 6.0             | 27.0                  | 133.0       |                     |
| 6.5             | 26.5                  | 137.6       |                     |
| 7.0             | 26.0                  | 142.4       |                     |
| 7.5             | 25.5                  | 147.4       |                     |
| 8.0             | 25.0                  | 152.6       |                     |
| 8.5             | 24.5                  | 157.6       |                     |
| 9.0             | 24.0                  | 162.6       |                     |
| 9.5             | 23.5                  | 167.8       |                     |
| 10.0            | 23.0                  | 173.0       |                     |
| 10.5            | 22.5                  | 178.0       |                     |
| 11.0            | 22.0                  | 183.4       |                     |
| 11.5            | 21.5                  | 188.8       |                     |
| 12.0            | 21.0                  | 194.2       |                     |
| 12.5            | 20.5                  | 200.2       |                     |
| 13.0            | 20.0                  | 206.6       | Current Lift SBD300 |
| 13.5            | 19.5                  | 213.4       |                     |
| 14.0            | 19.0                  | 221.0       |                     |
| 14.5            | 18.5                  | 228.8       |                     |
| 15.0            | 18.0                  | 236.2       | Max suggested Lift  |
| 15.5            | 17.5                  | 244.6       |                     |
| 16.0            | 17.0                  | 254.4       |                     |
| 16.3            | 16.7                  | Coil Bound! |                     |

***Please be aware that Technical Support involving our Technicians is chargeable***